




FDV SPEC SHEET

Leila C Surface

Art. no: 101370-70-2



Leila C Surface



Art. no: 101370-70-2

LIGHT TECHNICAL

| | |
|--------------------------|-------|
| Lumen Output: | 4633 |
| Lumen LED (tc=25): | 6100 |
| Beam Angle: | 70° |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|-------------|------------------|
| Connection: | QuickConnect |
| Mounting: | Ceiling, Surface |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| Dimming: | None |
| System Power [W]: | 42 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 28 |
| Max load pr circuit - B16: | 52 |
| Max load pr circuit - C10: | 35 |
| Max load pr circuit - C16: | 65 |
| Inrush current I _{max} [A]: | 10 |
| Inrush current time [μs]: | 100 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 1050 |



FDV SPEC SHEET

Leila C Surface

Art. no: 101370-70-2



PRODUCT

| | |
|-------------------------------|----------------|
| To be recessed in insulation: | No |
| Ingress Protection: | IP20 |
| Impact Protection: | IK00 |
| Operating Temperature [°C]: | -25 - 50 |
| Lifetime [h]: | L80B10: 60 000 |
| Color: | Black |
| Height [mm]: | 150 |
| Width [mm]: | 210 |
| Weight [kg]: | 1,9 |