




FDV SPEC SHEET

Tania Mini Slim

Art. no: 101910-36-21-p



Tania Mini Slim



Art. no: 101910-36-21-p

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	681
Lumen LED (tc=25):	850
Beam Angle:	36°
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Track 1-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	Phase-Cut
Flickerfree:	Yes
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	9
System Voltage [V]:	230V 50Hz
Dimming Phasecut Type:	Trailing edge
Protection Class:	1
Max load pr circuit - B16:	125
Max load pr circuit - C10:	200
Max load pr circuit - C16:	125
Inrush current Imax [A]:	5
Inrush current time [µs]:	100
Voltage Forward Min [V]:	32,3
Voltage Forward Max [V]:	38,1



FDV SPEC SHEET

Tania Mini Slim

Art. no: 101910-36-21-p



PRODUCT	
Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	Brushed Brass
Height [mm]:	142
Diameter [mm]:	42
Weight [kg]:	0,3
Housing Material :	Aluminium