



## PRODUCT SHEET


Icarus 500lm 927 36° 7W WH phasecut Isosafe 8-pack

Art. no: 101975-36-3

# NORLUX®


Lighting Solutions

# Icarus 500lm 927 36° 7W WH phasecut Isosafe 8-pack



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	7W
CCT (Color Temperature):	2700K
CRI / Ra:	95
Lumen Output:	456lm
Lumen LED (tc=25):	500lm
Beam Angle:	36°
Lens (Diffuser):	Clear
Dimming:	Phase-Cut
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Ceiling
Cut-out [mm]:	Ø68-83mm
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	62lm/W
UGR (<=):	22
MacAdam (SDCM):	3
Color:	White
Height [mm]:	44mm
Diameter [mm]:	90mm
Weight [kg]:	0,3kg
To be recessed in insulation:	Yes, recessed in insulation



7W downlight that can be installed directly into insulation. Cutout Ø68-83mm makes it perfect for rehab and new installation. Tilttable 25°, CRI>95 and flickerfree phasecut driver. 8-pack with driver for each downlighth.