



FDV SPEC SHEET

Stream Y

Art. no: 102452-02-ddd



Stream Y



Art. no: 102452-02-ddd

LIGHT TECHNICAL		ELECTRICAL DATA	
Lightsource Type:	LED (built in)	Dimming:	DALI2
Lumen Output:	6600	Dimming Output Type:	Amplitude Modulation
Lumen LED (tc=25):	7200	Flickerfree:	Yes
Beam Angle:	120°	Standby power Psb (W) <:	0,5
CCT (Color Temperature):	4000	Flicker metric (Pst LM) <:	1
CRI / Ra:	80	Stroboscopic effect metric (SVM) <	0,4
Color Code:	840	System Power [W]:	42
MacAdam (SDCM):	3	System Voltage [V]:	230V 50Hz
Lens (Diffuser):	PC Opal	Protection Class:	1
		Max load pr circuit - B10:	13
		Max load pr circuit - B16:	20
		Max load pr circuit - C10:	21
		Max load pr circuit - C16:	34
		Leakage current [mA]:	0,42
		Inrush current time [µs]:	296
		Socket / Cap-Base:	N/A
		Current Output [mA]:	300mA



FDV SPEC SHEET

Stream Y

Art. no: 102452-02-ddd



PRODUCT	
Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Grey
Length [mm]:	1536
Height [mm]:	80
Width [mm]:	76
Housing Material :	Polycarbonate

MOUNTING / CONNECTION	
Connection:	Terminalx2
Through-wiring (mm2):	5x2,5
Mounting:	Suspended, Surface