



PRODUCT SHEET

Stream Y NWC 7200lm 840 Opal 120° 42W 5x2,5 IP65 L:1536mm

Art. no: 102452-NW-02



Stream Y NWC 7200lm 840 Opal 120° 42W 5x2,5 IP65 L:



Stream Y NWC is an IP65 sealed industrial luminaire for ceiling or pendant mounting using wire (optional). The luminaire has many applications such as garage, industry, and warehouse. The luminaire has through-wiring (5x2.5 mm²), ensuring efficient installation without tools. With Norlux Wireless Connect integrated in the luminaire, you have modern lighting control technology without the need for extra cabling. This opens up possibilities for control, dimming, individual grouping, and sensor technology completely wirelessly with Bluetooth communication, using the Norlux Wireless Connect system for control. Simple programming via smartphone (iOS or Android)



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	42W
CCT (Color Temperature):	4000K
CRI / Ra:	80
Lumen LED (tc=25):	7200lm
Beam Angle:	120°
Lens (Diffuser):	PC Opal
Dimming:	Norlux Wireless Connect
System Voltage [V]:	230V 50Hz
Connection:	Terminalx2
Mounting:	Suspended, Surface
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	157lm/W
MacAdam (SDCM):	3
Color:	Grey
Length [mm]:	1536mm
Height [mm]:	80mm
Width [mm]:	76mm
Weight [kg]:	2,04kg