



**FDV SPEC SHEET**  
Universal G2 NWC IP44  
Art. no: 102471-NW-105-3



## Universal G2 NWC IP44



Art. no: 102471-NW-105-3

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2200
Lumen LED (tc=25):	2450
Beam Angle:	105°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	22

### MOUNTING / CONNECTION

Connection:	Quickconnectx2
Through-wiring (mm2):	5x2,5
Mounting:	Ceiling, Surface

### ELECTRICAL DATA

Dimming:	Norlux Wireless Connect
Dimming Output Type:	AM+PWM
Output Hz:	400-20KHz
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	20
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	52
Max load pr circuit - B16:	83
Max load pr circuit - C10:	52
Max load pr circuit - C16:	83
Leakage current [mA]:	0,7
Inrush current Imax [A]:	6,5
Inrush current time [µs]:	172
Socket / Cap-Base:	N/A
Current Output [mA]:	50mA



## FDV SPEC SHEET

Universal G2 NWC IP44  
Art. no: 102471-NW-105-3



PRODUCT	
Ingress Protection:	IP44
Impact Protection:	IK07
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9003
Length [mm]:	600
Height [mm]:	52
Width [mm]:	156
Weight [kg]:	1,43
Housing Material :	Metal