



## FDV SPEC SHEET

C Line

Art. no: 102517-2-E-01-1



## C Line



Art. no: 102517-2-E-01-1

### LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	17000
Lumen LED (tc=25):	18700
Beam Angle:	90°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

### ELECTRICAL DATA

Dimming:	Emergency
Flickerfree:	Yes
System Power [W]:	100/83/65/57/48
Preset Power [W]:	83
System Voltage [V]:	230V 50Hz
Protection Class:	1
Current Output [mA]:	75
Emergency light [h]:	3 hours
Emergency light testing:	Selftest
Emergency lumen out [lm]:	300

### MOUNTING / CONNECTION

Connection:	Quickconnectx2
Mounting:	Surface, Ceiling



## FDV SPEC SHEET

C Line

Art. no: 102517-2-E-01-1



PRODUCT	
Ingress Protection:	IP23
Impact Protection:	IK10
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Steel
Length [mm]:	1550
Height [mm]:	50
Width [mm]:	76
Weight [kg]:	2,54