





**FDV SPEC SHEET**  
Benu Slim Office Pullswitch  
Art. no: 102521-140-2



## Benu Slim Office Pullswitch



Art. no: 102521-140-2

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	6066
Lumen LED (tc=25):	8216.75
Beam Angle:	120° / 80°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	19

### MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Through-wiring (mm2):	3x0,75

### ELECTRICAL DATA

Dimming:	DALI2
Flickerfree:	Yes
System Power [W]:	50
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	60
Voltage Forward Min [V]:	2,5
Voltage Forward Max [V]:	3



## FDV SPEC SHEET

Benu Slim Office Pullswitch

Art. no: 102521-140-2



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK02
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Length [mm]:	1206
Height [mm]:	70
Width [mm]:	35
Weight [kg]:	1,95
Housing Material :	Aluminium 6063