





## **Orion G2**







| SPECIFICATIONS           |                    |
|--------------------------|--------------------|
| Lightsource Type:        | LED (replaceable)  |
| System Power [W]:        | 35/30/24/19W       |
| CCT (Color Temperature): | 4000K              |
| CRI / Ra:                | 80                 |
| Lumen Output:            | 5600lm             |
| Lumen LED (tc=25):       | 6200lm             |
| Beam Angle:              | 120°               |
| Lens (Diffuser):         | Frosted            |
| Dimming:                 | None               |
| Flickerfree:             | Yes                |
| System Voltage [V]:      | 230V 50Hz          |
| Connection:              | QuickConnect       |
| Mounting:                | Suspended, Surface |
| Lifetime [h]:            | L80B10: 100 000h   |
| Lumen/W:                 | 160lm/W            |
| MacAdam (SDCM):          | 3                  |
| Through-wiring (mm2):    | 5x2,5              |
| Color:                   | Grey               |
| Length [mm]:             | 1225mm             |
| Height [mm]:             | 60mm               |
| Width [mm]:              | 65mm               |
| Weight [kg]:             | 0,97kg             |



Orion is an energy-efficient industrial luminaire. With IP65 and IK08, it is suitable for use in tough environments both indoors and outdoors, in wet and dusty surroundings. The luminaire is equipped with a power switch where you can easily change the output via a DIP switch. Through-wiring for series installation and QuickConnect for easy installation. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.