




FDV SPEC SHEET

Orion G2 NWC 6400lm 840 40W 120° 1500mm

Art. no: 102616-NW-120-1



Orion G2 NWC 6400lm 840 40W 120° 1500mm



Art. no: 102616-NW-120-1

LIGHT TECHNICAL		ELECTRICAL DATA	
Lightsource Type:	LED (replaceable)	Dimming:	Norlux Wireless Connect
Lumen Output:	5800	Dimming Output Type:	AM+PWM
Lumen LED (tc=25):	6400	Output Hz:	400-20KHz
Beam Angle:	120°	Flickerfree:	Yes
CCT (Color Temperature):	4000	Standby power Psb (W) <:	0,5
CRI / Ra:	80	Flicker metric (Pst LM) <:	1
Color Code:	840	Stroboscopic effect metric (SVM) <	0,4
MacAdam (SDCM):	3	System Power [W]:	40
Lens (Diffuser):	Frosted	System Voltage [V]:	230V 50Hz
		Protection Class:	1
		Max load pr circuit - B10:	39
		Max load pr circuit - B16:	63
		Max load pr circuit - C10:	39
		Max load pr circuit - C16:	63
		Leakage current [mA]:	0,7
		Inrush current Imax [A]:	6,6
		Inrush current time [µs]:	162
		Socket / Cap-Base:	N/A
		Current Output [mA]:	60



FDV SPEC SHEET

Orion G2 NWC 6400lm 840 40W 120° 1500mm
Art. no: 102616-NW-120-1



PRODUCT	
Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Grey
RAL:	RAL7035
Length [mm]:	1525
Height [mm]:	60
Width [mm]:	65
Weight [kg]:	1,3

MOUNTING / CONNECTION	
Connection:	QuickConnect
Through-wiring (mm2):	5x2,5
Mounting:	Suspended, Surface