




FDV SPEC SHEET

Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø160-170mm

Art. no: 102620-S-60-3



Nereus M/S 1850lm 830/840/857 60° 12W WH PIR Ø16



Art. no: 102620-S-60-3

LIGHT TECHNICAL

| | |
|---------------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 1660 |
| Lumen LED (tc=25): | 1850 |
| Beam Angle: | 60° |
| CCT (Color Temperature): | 3/4/5700 |
| Preset CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830/840/857 |

MOUNTING / CONNECTION

| | |
|---------------|-------------------|
| Connection: | QuickConnect |
| Cut-out [mm]: | Ø160-170mm |
| Mounting: | Recessed, Ceiling |

PRODUCT

| | |
|-------------------------------|-----------------|
| To be recessed in insulation: | Not applicable |
| Ingress Protection: | IP44 |
| Operating Temperature [°C]: | -20 - 40 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | White |
| RAL: | RAL9016 |

ELECTRICAL DATA

| | |
|-----------------------|--------------|
| UGR (<=): | 19 |
| Dimming: | Sensor (PIR) |
| System Power [W]: | 12 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Leakage current [mA]: | 0,16 |
| Socket / Cap-Base: | N/A |