



## FDV SPEC SHEET

NDL240-B

Art. no: 102793-2-60-3



## NDL240-B



Art. no: 102793-2-60-3

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2600
Lumen LED (tc=25):	2800
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

### MOUNTING / CONNECTION

Connection:	EPN0024
Cut-out [mm]:	195-230
Mounting:	Recessed, Ceiling

### ELECTRICAL DATA

UGR (<=):	19
Dimming:	Depending on Driver
Flickerfree:	Yes
System Power [W]:	25
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	650
Voltage Forward Min [V]:	30
Voltage Forward Max [V]:	40
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A



## FDV SPEC SHEET

NDL240-B

Art. no: 102793-2-60-3



PRODUCT	
To be recessed in insulation:	Not applicable
Ingress Protection:	IP44
Impact Protection:	IK06
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	240
Height [mm]:	142
Width [mm]:	240
Diameter [mm]:	240
Weight [kg]:	0,93
Housing Material :	Aluminium
Diffuser Material:	Aluminium 6063