



FDV SPEC SHEET

Mika29 Pole

Art. no: 102944-5



Mika29 Pole



Art. no: 102944-5

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	1875
Lumen LED (tc=25):	1900
Beam Angle:	140°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	4
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Cable 6m
-------------	----------

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
System Power [W]:	15
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A



FDV SPEC SHEET

Mika29 Pole

Art. no: 102944-5



PRODUCT

Ingress Protection:	IP66
Impact Protection:	IK08
Corrosion Class:	C4
Wind force (EPA) [m2] at 0°:	0,146
Operating Temperature [°C]:	-25 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Antracite
RAL:	RAL7016
Length [mm]:	500
Height [mm]:	523
Width [mm]:	500
Diameter [mm]:	500
Weight [kg]:	8,4