





Montana M







C € ☐ IP66 230V IK08 IK08

Lightsource Type: LED (built in) System Power [W]: 90W CCT (Color Temperature): 3000K CRI / Ra: 70 Lumen Output: 12600lm Lumen LED (tc=25): 13860lm Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	SPECIFICATIONS	
CCT (Color Temperature): 3000K CRI / Ra: 70 Lumen Output: 12600lm Lumen LED (tc=25): 13860lm Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lightsource Type:	LED (built in)
CRI / Ra: 70 Lumen Output: 12600lm Lumen LED (tc=25): 13860lm Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	System Power [W]:	90W
Lumen Output: 12600lm Lumen LED (tc=25): 13860lm Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	CCT (Color Temperature):	3000K
Lumen LED (tc=25): 13860lm Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	CRI / Ra:	70
Beam Angle: 143°*65° Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lumen Output:	12600lm
Lens (Diffuser): PMMA Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lumen LED (tc=25):	13860lm
Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Beam Angle:	143°*65°
Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lens (Diffuser):	PMMA
System Voltage [V]: 230V 50Hz Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Dimming:	None
Connection: Cable 10m Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Flickerfree:	Yes
Mounting: Mast Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	System Voltage [V]:	230V 50Hz
Cut-out [mm]: n/amm Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Connection:	Cable 10m
Lifetime [h]: L80B10: 100 000h Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Mounting:	Mast
Lumen/W: 140lm/W MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Cut-out [mm]:	n/amm
MacAdam (SDCM): 5 Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lifetime [h]:	L80B10: 100 000h
Color: Grey Length [mm]: 665mm Height [mm]: 135mm	Lumen/W:	140lm/W
Length [mm]: 665mm Height [mm]: 135mm	MacAdam (SDCM):	5
Height [mm]: 135mm	Color:	Grey
	Length [mm]:	665mm
	Height [mm]:	135mm
Width [mm]: 250mm	Width [mm]:	250mm
Diameter [mm]: 76mm	Diameter [mm]:	76mm
Weight [kg]: 7kg	Weight [kg]:	7kg
Emergency light [h]: No Emergency light	Emergency light [h]:	No Emergency light
Emergency light testing: N/A	Emergency light testing:	N/A

Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.