





Montana M







C € ☐ IP66 230V IK08 →

htsource Type: LED (bit stem Power [W]: 90W ((Color Temperature): 3000K / Ra: 70 men Output: 12600b	uilt in)
T (Color Temperature): 3000K / Ra: 70 men Output: 12600k	
/ Ra: 70 men Output: 12600k	
men Output: 12600l	
·	
	n
nen LED (tc=25): 13860l	n
am Angle: 156°*5	4°
ns (Diffuser): PMMA	
nming: None	
ckerfree: Yes	
stem Voltage [V]: 230V 5	OHz
nnection: Cable 1	0m
unting: Mast	
r-out [mm]: n/amm	1
etime [h]:	: 100 000h
men/W: 140lm/	W
cAdam (SDCM): 5	
or: Grey	
ngth [mm]: 665mm	ı
ght [mm]: 135mm	
dth [mm]: 250mm	1
meter [mm]: 76mm	
ight [kg]: 7kg	
ergency light [h]: No Em	ergency light

Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.