



FDV SPEC SHEET

Cosma

Art. no: 103081-04-3



Cosma



Art. no: 103081-04-3

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	3060
Lumen LED (tc=25):	3300
Beam Angle:	120°
CCT (Color Temperature):	30/35/4000K
CRI / Ra:	80
Color Code:	830/835/840
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	24

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Wall, Ceiling

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
System Power [W]:	25/20/15
Preset Power [W]:	25
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	100



FDV SPEC SHEET

Cosma

Art. no: 103081-04-3



PRODUCT	
Ingress Protection:	IP44
Impact Protection:	IK10
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9003
Length [mm]:	400
Height [mm]:	70
Width [mm]:	400
Weight [kg]:	1,33