



FDV SPEC SHEET

T-Line Louvre

Art. no: 103130-60-3



T-Line Louvre



Art. no: 103130-60-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	10550
Lumen LED (tc=25):	11200
Beam Angle:	60°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Lens
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Mounting:	Suspended

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	0,016
Stroboscopic effect metric (SVM) <	0,041
System Power [W]:	70-40
Preset Power [W]:	70
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	13
Max load pr circuit - B16:	21
Max load pr circuit - C10:	21
Max load pr circuit - C16:	34
Leakage current [mA]:	0,54
Inrush current I _{max} [A]:	20,94
Inrush current time [μs]:	254
Current Output [mA]:	500



FDV SPEC SHEET

T-Line Louvre

Art. no: 103130-60-3



PRODUCT	
Ingress Protection:	IP40
Impact Protection:	IK03
Operating Temperature [°C]:	-25 - 60
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Length [mm]:	1665
Height [mm]:	44
Width [mm]:	62
Weight [kg]:	2,3
Housing Material :	Aluminium
Diffuser Material:	PMMA