




FDV SPEC SHEET

Cold 10 Mini

Art. no: 1111-50-2



189x27mm



Cold 10 Mini



Art. no: 1111-50-2

LIGHT TECHNICAL	
Lightsource Type:	LED (built in)
Lumen Output:	1170
Lumen LED (tc=25):	2000
Beam Angle:	50°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	927
Lens (Diffuser):	N/A
MOUNTING / CONNECTION	
Connection:	EPN0024
Cut-out [mm]:	189*27
Mounting:	Recessed, Ceiling



FDV SPEC SHEET

Cold 10 Mini

Art. no: 1111-50-2



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK00
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9003
Length [mm]:	196
Height [mm]:	50
Width [mm]:	33
Weight [kg]:	0,54
Housing Material :	Aluminium
Diffuser Material:	Polycarbonate

ELECTRICAL DATA	
UGR (<=):	9
Dimming:	Phase-Cut
Dimming Output Type:	Amplitude Modulation
Dimming Phasecut Type:	Leading / Trailing edge
Flickerfree:	No
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	21
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	52
Max load pr circuit - C16:	84
Leakage current [mA]:	0,7
Inrush current Imax [A]:	5
Inrush current time [µs]:	300
Current Output [mA]:	7
Voltage Forward Min [V]:	27
Voltage Forward Max [V]:	32