



## PRODUCT SHEET

Torres Mini

Art. no: 17030-7-40-2


# NORLUX®

Lighting Solutions

## Torres Mini



125mm



This is by far our most popular mini" downlight and it offers huge flexibility, tiltable up to 25 degrees. This downlight has a recessed light source giving a minimum of stray light. The Torres Mini can be supplied with a variety of connector solutions.



### SPECIFICATIONS

|                               |                       |
|-------------------------------|-----------------------|
| Lightsource Type:             | LED (built in)        |
| System Power [W]:             | 22W                   |
| CCT (Color Temperature):      | 3000K                 |
| CRI / Ra:                     | 80                    |
| Lumen Output:                 | 2780lm                |
| Lumen LED (tc=25):            | 3650lm                |
| Beam Angle:                   | 40°                   |
| Lens (Diffuser):              | Clear                 |
| Dimming:                      | None                  |
| System Voltage [V]:           | 230V 50Hz             |
| Connection:                   | 18i3 Quick connection |
| Mounting:                     | Recessed, Ceiling     |
| Cut-out [mm]:                 | Ø125mm                |
| Color:                        | Black                 |
| Length [mm]:                  | 138mm                 |
| Height [mm]:                  | 86mm                  |
| Width [mm]:                   | 94mm                  |
| To be recessed in insulation: | No                    |