



## PRODUCT SHEET

Trimo Mini

Art. no: 18020-7-40-3-ddd


# NORLUX®

Lighting Solutions

## Trimo Mini



112mm



Our Trimo range of downlights guarantees a minimum of stray light. This is accomplished by using a recessed LED light source. This model requires a hole dimension of 112mm in diameter making it very versatile providing very powerful light. The Trimo Mini has a 18i3 connector and is supplied with a variety of connector solutions.



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	24W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	2890lm
Lumen LED (tc=25):	3650lm
Beam Angle:	40°
Lens (Diffuser):	Clear
Dimming:	DALI
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	18i5 DALI Quick connection
Mounting:	Recessed, Ceiling
Cut-out [mm]:	Ø112mm
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	121lm/W
MacAdam (SDCM):	3
Color:	White
Height [mm]:	110mm
Width [mm]:	122mm
Weight [kg]:	0,7kg
To be recessed in insulation:	No