



FDV SPEC SHEET

Pollux Master / Slave

Art. no: 2119-MS-120-3



Pollux Master / Slave



Art. no: 2119-MS-120-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2384
Lumen LED (tc=25):	2800
Beam Angle:	120°
CCT (Color Temperature):	3/4/5700
CRI / Ra:	80
Color Code:	830/840/857
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Ceiling, Surface

ELECTRICAL DATA

Dimming:	MW RF Master-Slave Dim
Dimming Output Type:	Amplitude Modulation
System Power [W]:	25
System Voltage [V]:	230V 50Hz
Protection Class:	2



FDV SPEC SHEET

Pollux Master / Slave

Art. no: 2119-MS-120-3



PRODUCT	
Ingress Protection:	IP54
Impact Protection:	IK10
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9016
Height [mm]:	58
Diameter [mm]:	300
Weight [kg]:	1,09
Housing Material :	Polycarbonate