



FDV SPEC SHEET

Phoenix NWC

Art. no: 3450-NW-140-3



Phoenix NWC



Art. no: 3450-NW-140-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4338.54
Lumen LED (tc=25):	130
Beam Angle:	360°
CCT (Color Temperature):	3000-4000K
CRI / Ra:	90
Color Code:	930/940
MacAdam (SDCM):	3
Lens (Diffuser):	None
UGR (<=):	10

MOUNTING / CONNECTION

Connection:	Cable 3m
Mounting:	Pendant



FDV SPEC SHEET

Phoenix NWC

Art. no: 3450-NW-140-3



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP20	Dimming Output Type:	Amplitude Modulation
Impact Protection:	IK06	Output Hz:	NA
Operating Temperature [°C]:	45 -	Flickerfree:	Yes
Lifetime [h]:	50 000	Standby power Psb (W) <:	0,5
Color:	White	Flicker metric (Pst LM) <:	0
RAL:	RAL9003	Stroboscopic effect metric (SVM) <	0,004
Length [mm]:	1285	System Power [W]:	60
Height [mm]:	76	System Voltage [V]:	230V 50Hz / 176-275VDC
Width [mm]:	48	Protection Class:	1
Weight [kg]:	4,12	Max load pr circuit - B10:	26
Housing Material :	Aluminium 6063	Max load pr circuit - B16:	41
Diffuser Material:	Polycarbonate	Max load pr circuit - C10:	26
Material 2:	Steel	Max load pr circuit - C16:	41
		Leakage current [mA]:	0,64
		Inrush current Imax [A]:	9,63
		Inrush current time [µs]:	156
		Socket / Cap-Base:	N/A
		Current Output [mA]:	125
		Voltage Forward Min [V]:	9,4
		Emergency light [h]:	No Emergency light
		Emergency light testing:	N/A