




## **Tania Mini 3-Circuit**





Tania Mini is a small spotlight in a contemporary design. Perfect for use at home and in other commercial settings. Front ring is sold separately. This version is with LED COB and no changeable lightbulb.

SPECIFICATIONS Lightsource Type: LED (built in) System Power [W]: 14,5W CCT (Color Temperature): 2700K CRI / Ra: 90 Lumen Output: 1050lm Lumen LED (tc=25): 1450lm Beam Angle: 36° Lens (Diffuser): Clear Dimming: Phase-Cut Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 3	CE P20 SOHZ	A** - A
System Power [W]:       14,5W         CCT (Color Temperature):       2700K         CRI / Ra:       90         Lumen Output:       1050lm         Lumen LED (tc=25):       1450lm         Beam Angle:       36°         Lens (Diffuser):       Clear         Dimming:       Phase-Cut         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         MacAdam (SDCM):       3	SPECIFICATIONS	
CCT (Color Temperature):       2700K         CRI / Ra:       90         Lumen Output:       1050lm         Lumen LED (tc=25):       1450lm         Beam Angle:       36°         Lens (Diffuser):       Clear         Dimming:       Phase-Cut         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         MacAdam (SDCM):       3	Lightsource Type:	LED (built in)
CRI / Ra:       90         Lumen Output:       1050lm         Lumen LED (tc=25):       1450lm         Beam Angle:       36°         Lens (Diffuser):       Clear         Dimming:       Phase-Cut         Flickerfree:       Yes         System Voltage [V]:       230V 50Hz         Connection:       Track 3-Circuit         Mounting:       Track, Ceiling         Lifetime [h]:       L80B10: 100 000h         MacAdam (SDCM):       3	System Power [W]:	14,5W
Lumen Output: 1050lm  Lumen LED (tc=25): 1450lm  Beam Angle: 36°  Lens (Diffuser): Clear  Dimming: Phase-Cut  Flickerfree: Yes  System Voltage [V]: 230V 50Hz  Connection: Track 3-Circuit  Mounting: Track, Ceiling  Lifetime [h]: L80B10: 100 000h  MacAdam (SDCM): 3	CCT (Color Temperature):	2700K
Lumen LED (tc=25): 1450lm  Beam Angle: 36°  Lens (Diffuser): Clear  Dimming: Phase-Cut  Flickerfree: Yes  System Voltage [V]: 230V 50Hz  Connection: Track 3-Circuit  Mounting: Track, Ceiling  Lifetime [h]: L80B10: 100 000h  MacAdam (SDCM): 3	CRI / Ra:	90
Beam Angle: 36° Lens (Diffuser): Clear Dimming: Phase-Cut Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 3	Lumen Output:	1050lm
Lens (Diffuser):  Dimming: Phase-Cut  Flickerfree: Yes  System Voltage [V]: Connection: Track 3-Circuit  Mounting: Track, Ceiling  Lifetime [h]: MacAdam (SDCM):  3	Lumen LED (tc=25):	1450lm
Dimming: Phase-Cut  Flickerfree: Yes  System Voltage [V]: 230V 50Hz  Connection: Track 3-Circuit  Mounting: Track, Ceiling  Lifetime [h]: L80B10: 100 000h  MacAdam (SDCM): 3	Beam Angle:	36°
Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 3	Lens (Diffuser):	Clear
System Voltage [V]: 230V 50Hz Connection: Track 3-Circuit Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 3	Dimming:	Phase-Cut
Connection: Track 3-Circuit  Mounting: Track, Ceiling  Lifetime [h]: L80B10: 100 000h  MacAdam (SDCM): 3	Flickerfree:	Yes
Mounting: Track, Ceiling Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 3	System Voltage [V]:	230V 50Hz
Lifetime [h]: L80B10: 100 000h  MacAdam (SDCM): 3	Connection:	Track 3-Circuit
MacAdam (SDCM): 3	Mounting:	Track, Ceiling
	Lifetime [h]:	L80B10: 100 000h
Color: Pruchod Prace	MacAdam (SDCM):	3
Cotor. Brusileu Brass	Color:	Brushed Brass
Length [mm]: 147mm	Length [mm]:	147mm
Diameter [mm]: 60mm	Diameter [mm]:	60mm