



FDV SPEC SHEET

Izar

Art. no: 3932-01-3-ddd



Izar



Art. no: 3932-01-3-ddd

LIGHT TECHNICAL

Lumen Output:	5588
Lumen LED (tc=25):	6500
Beam Angle:	90° / 110°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	18

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Pendant, Ceiling, Surface

PRODUCT

Ingress Protection:	IP20
Impact Protection:	IK06
Lifetime [h]:	L80B10: 50.000
Color:	White
Height [mm]:	82
Width [mm]:	600
Weight [kg]:	7,29

ELECTRICAL DATA

Dimming:	DALI
System Power [W]:	54
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	11
Max load pr circuit - B16:	17
Max load pr circuit - C10:	13
Max load pr circuit - C16:	21
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	30
Inrush current time [μs]:	120
Socket / Cap-Base:	N/A