




## FDV SPEC SHEET

Columba

Art. no: 5712-04-3-ddd



## Columba



A++

Art. no: 5712-04-3-ddd

### LIGHT TECHNICAL

Lumen Output:	14805
Beam Angle:	90°x90°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3

### PRODUCT

Ingress Protection:	IP65
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 35
Lifetime [h]:	L80B50: 100 000
Color:	White
Length [mm]:	1190
Height [mm]:	80
Width [mm]:	114
Weight [kg]:	2,2

### ELECTRICAL DATA

Dimming:	DALI
Dimming Output Type:	Amplitude Modulation
System Power [W]:	86
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	6
Max load pr circuit - B16:	10
Max load pr circuit - C10:	10
Max load pr circuit - C16:	16
Leakage current [mA]:	0,46
Inrush current I <sub>max</sub> [A]:	33
Inrush current time [μs]:	280
Socket / Cap-Base:	N/A

### MOUNTING / CONNECTION

Cut-out [mm]:	NA
Mounting:	Suspended, Ceiling, Surface