



FDV SPEC SHEET
Ledline
Art. no: 805004-03-2-ddd



Ledline



Art. no: 805004-03-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 6800 |
| Lumen LED (tc=25): | 7100 |
| Beam Angle: | 110 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Opal |

MOUNTING / CONNECTION

| | |
|-------------|------------------------------------|
| Connection: | LEDLine 5-pin |
| Mounting: | Recessed, Pendant, Ceiling, Surfac |



FDV SPEC SHEET

Ledline
Art. no: 805004-03-2-ddd



| PRODUCT | |
|---------------------|-----------------|
| Ingress Protection: | IP40 |
| Impact Protection: | IK08 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| Length [mm]: | 2400 |
| Height [mm]: | 84 |
| Width [mm]: | 56 |
| Weight [kg]: | 5,95 |

| ELECTRICAL DATA | |
|------------------------------------|----------------------|
| Dimming: | DALI |
| Dimming Output Type: | Amplitude Modulation |
| Flickerfree: | Yes |
| Standby power Psb (W) <: | 0,5 |
| Flicker metric (Pst LM) <: | 0,002 |
| Stroboscopic effect metric (SVM) < | 0,005 |
| System Power [W]: | 70 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Max load pr circuit - B10: | 20 |
| Max load pr circuit - B16: | 32 |
| Max load pr circuit - C10: | 20 |
| Max load pr circuit - C16: | 32 |
| Leakage current [mA]: | 0,7 |
| Inrush current Imax [A]: | 8,54 |
| Inrush current time [µs]: | 214 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 2000 |
| Voltage Forward Min [V]: | 32 |
| Voltage Forward Max [V]: | 48 |