



FDV SPEC SHEET

Galactic C
Art. no: 9057-4-02-2-ddd



Galactic C



Art. no: 9057-4-02-2-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3300
Lumen LED (tc=25):	4200
Beam Angle:	85°
CCT (Color Temperature):	2700-3000K
CRI / Ra:	90
Color Code:	927/930
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.

MOUNTING / CONNECTION

Connection:	Terminal
Cut-out [mm]:	220-250
Mounting:	Partial-recessed, Surface, Pendant

ELECTRICAL DATA

Dimming:	DALI
Dimming Output Type:	Amplitude Modulation
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	40
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	22
Max load pr circuit - B16:	35
Max load pr circuit - C10:	22
Max load pr circuit - C16:	35
Leakage current [mA]:	0,7
Inrush current Imax [A]:	20
Inrush current time [µs]:	120
Socket / Cap-Base:	N/A
Current Output [mA]:	1050mA



FDV SPEC SHEET

Galactic C
Art. no: 9057-4-02-2-ddd



PRODUCT	
Ingress Protection:	IP40
Impact Protection:	IK03
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Length [mm]:	400
Height [mm]:	102
Width [mm]:	400
Diameter [mm]:	400
Weight [kg]:	3,2
Housing Material :	Aluminium 6063
Diffuser Material:	Polycarbonate
Material 2:	SPCC