



FDV SPEC SHEET
Galactic C
Art. no: 9057-TW-02-2-ddd



Galactic C



Art. no: 9057-TW-02-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen LED (tc=25): | 4200 |
| Beam Angle: | 85° |
| CCT (Color Temperature): | 2700-6500K |
| CRI / Ra: | 80 |
| Color Code: | 827-865 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Micropris. |

MOUNTING / CONNECTION

| | |
|-------------|------------------------------------|
| Connection: | QuickConnect |
| Mounting: | Partial-recessed, Pendant, Surface |

PRODUCT

| | |
|-----------------------------|-----------------|
| Ingress Protection: | IP40 |
| Operating Temperature [°C]: | -20 - 45 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| RAL: | RAL9005 |
| Width [mm]: | 400 |
| Housing Material : | Aluminium |

ELECTRICAL DATA

| | |
|--------------------------------------|----------------------|
| Dimming: | DALI2 |
| Dimming Output Type: | Amplitude Modulation |
| Flicker metric (Pst LM) <: | 1 |
| Stroboscopic effect metric (SVM) < | 0,4 |
| System Power [W]: | 40 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 14 |
| Max load pr circuit - B16: | 23 |
| Inrush current I _{max} [A]: | 27 |
| Inrush current time [μs]: | 205 |
| Socket / Cap-Base: | N/A |