



## FDV SPEC SHEET

Trunk Line  
Art. no: CFTL-1550-30NR-08-3



## Trunk Line



Art. no: CFTL-1550-30NR-08

### LIGHT TECHNICAL

|                          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen Output:            | 8473           |
| Lumen LED (tc=25):       | 9300           |
| Beam Angle:              | 60             |
| CCT (Color Temperature): | 3000           |
| CRI / Ra:                | 80             |
| Color Code:              | 830            |
| Lens (Diffuser):         | Lens           |
| UGR (<=):                | 19             |

### MOUNTING / CONNECTION

|             |                    |
|-------------|--------------------|
| Connection: | Trunk 8-wires      |
| Mounting:   | Suspended, Ceiling |

### PRODUCT

|                     |                 |
|---------------------|-----------------|
| Ingress Protection: | IP20            |
| Lifetime [h]:       | L80B10: 100 000 |
| Color:              | White           |
| RAL:                | RAL9016         |
| Length [mm]:        | 1500            |

### ELECTRICAL DATA

|                                      |             |
|--------------------------------------|-------------|
| Dimming:                             | None        |
| Flickerfree:                         | Yes         |
| Flicker metric (Pst LM) <:           | 1           |
| Stroboscopic effect metric (SVM) <   | 0,4         |
| System Power [W]:                    | 50/45/40/35 |
| System Voltage [V]:                  | 230V 50Hz   |
| Protection Class:                    | 1           |
| Max load pr circuit - B10:           | 24          |
| Max load pr circuit - B16:           | 38          |
| Max load pr circuit - C10:           | 28          |
| Max load pr circuit - C16:           | 44          |
| Leakage current [mA]:                | 0,24        |
| Inrush current I <sub>max</sub> [A]: | 28          |
| Inrush current time [μs]:            | 110         |