



PRODUCT SHEET

Driver 700mA cc 30W 21-43V Phasecut AcTec 18i3 Male/EPN0034

Art. no: D70030NTF-03



Driver 700mA cc 30W 21-43V Phasecut AcTec 18i3 Male



SPECIFICATIONS

System Power [W]:	30W
Dimming:	Phase-Cut
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
Flickerfree:	Yes
CC or CV:	CC
CC [mA]:	700 - mA
CC (forward voltage driver) [V]:	21 - 43V
Max output voltage [V]:	54
Output Current Tolerance [%]:	5%
Current Ripple [%]:	2%
System Voltage [V]:	230V 50Hz V
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	7mA
Inrush current I _{max} [A]:	5A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Secondary Connection:	EPN0034 female
Length:	142mm
Height:	24mm
Width:	50mm



PRODUCT SHEET

Driver 700mA cc 30W 21-43V Phasecut AcTec 18i3 Male/EPN0034
Art. no: D70030NTF-03



Weight:	0,2kg
Operating Temperature [°C]:	-20 - 50