




PRODUCT FAMILY SHEET

Exilis II dim



Exilis II dim

Our LED tube luminaire with a built in LED driver makes installation a breeze. The Exilis II comes in a variety of lengths that can be easily be connected together without the use of tools, just by clicking the LED tubes together. The different lengths makes it very easy to make a continuous line of light regardless of the length of the surface. The Exilis II comes with a opal diffuser and phasecut dim. Max 500W for each feed.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
2615-2-01-3	15	1650		4000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2510-2-01-3	10	1100		3000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2610-2-01-3	10	1100		4000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2515-2-01-3	15	1650		3000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2520-2-01-3	20	2200		3000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2620-2-01-3	20	2200		4000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2605-2-01-3	5	550		4000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2505-2-01-3	5	550		3000	120°	Opal	80	White	Phase-Cut	xilis II 3-pin Connect
2510-01-3	10	1100		3000	120°	Opal	80	Aluminium	Phase-Cut	xilis II 3-pin Connect