



PRODUCT FAMILY SHEET

Trimo Mini



Trimo Mini

Our Trimo range of downlights guarantees a minimum of stray light. This is accomplished by using a recessed LED light source. This model requires a hole dimension of 112mm in diameter making it very versatile providing very powerful light. The Trimo Mini has a 18i3 connector and is supplied with a variety of connector solutions.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
18020-7-30-3- ddd	24	3650	3050	3000	30°	Clear	80	White	DALI	5 DALI Quick connect
18020-7-40-3- ddd	24	3650	2890	3000	40°	Clear	80	White	DALI	5 DALI Quick connect
18020-7-40-2- ddd	24	3650	2890	3000	40°	Clear	80	Black	DALI	5 DALI Quick connect
18020-7-40-3	24	3650	2890	3000	40°	Clear	80	White	None	18i3 Quick connectio
18020-7-24-2	24	3650	2940	3000	24°	Clear	80	Black	None	18i3 Quick connectio
18020-7-24-3	24	3650	2940	3000	24°	Clear	80	White	None	18i3 Quick connectio
18020-6-30-3- ddd	23	3450	2800	3000	30°	Clear	80	White	DALI	5 DALI Quick connect
18020-24-2	22	2314		3000	24°	Clear	80	Black	None	18i3 Quick connectio
18020-7-60-3- ddd	24	3650	2780	3000	40°	Clear	80	White	DALI	5 DALI Quick connect