



PRODUCT FAMILY SHEET

Zoom Mini Spotlight



Zoom Mini Spotlight

Zoom Mini is relatively small spotlight for use in track lighting systems. The unique zoom patent makes it possible to vary the beam angel between 5 - and 60 degrees making this model highly versatile. The Zoom Mini is available in both 2700 and 3000 Kelvin and is made from robust die-cast aluminum. Choose between on/off, phase cut and DALI dimming.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
7066-02-560-2	15	900		2700	5-60°	Clear	97	Black	Phase-Cut	Track 1-Circuit
7066-02-560-3	15	900		2700	5-60°	Clear	97	White	Phase-Cut	Track 1-Circuit
7064-02-560-3	15	1300		3000	5-60°	Clear	90	White	Phase-Cut	Track 3-Circuit
7067-560-2	15	900		3000	5-60°	Clear	97	Black	Phase-Cut	Track 1-Circuit
7063-02-560-3	15	1250	687	2700	5-60°	Clear	90	White	Phase-Cut	Track 3-Circuit
7063-02-560-2	15	1250		2700	5-60°	Clear	90	Black	Phase-Cut	Track 3-Circuit
7064-02-560-2	15	1300		3000	5-60°	Clear	90	Black	Phase-Cut	Track 3-Circuit
7066-560-3	15	900	687	2700	5-60°	Clear	97	White	Phase-Cut	Track 1-Circuit
7060-560-2	15	900	511-275	2700	5-60	Clear	80	Black	None	Track 3-Circuit
7060-560-3	15	900	511-276	2700	5-60	Clear	80	White	None	Track 3-Circuit
7063-02-560-3-ddd	15	1250		2700	5°-60°	Clear	90	White	DALI2	Track 3-Circuit
7063-02-560-2-ddd	15	1250		2700	5°-60°	Clear	90	Black	DALI2	Track 3-Circuit