



PRODUCT SHEET

Driver On/Off 700mA max 31W 25-45V 18i3 Male/ EPN0034

Art. no: 0300-10



Driver On/Off 700mA max 31W 25-45V 18i3 Male/ EPN

Tridonic On/Off driver preset at 700mA, max 31W.

Primary side 0,3m cable with 18i3 (male).

Secondary side EPN0034 (female).



SPECIFICATIONS

System Power [W]:	31W
Dimming:	None
CC or CV:	CC
CC [mA]:	700 - mA
CC (forward voltage driver) [V]:	25 - 45V
Max output voltage [V]:	60
Output Current Tolerance [%]:	7,5%
Current Ripple [%]:	5%
Current setting:	ADV Plug (Tridonic)
Expected Lifetime:	100000h
System Voltage [V]:	230V 50HzV
Protection Class:	1 or 2
Max load pr circuit - B10:	14
Max load pr circuit - B16:	24
Max load pr circuit - C10:	24
Max load pr circuit - C16:	40
Leakage current [mA]:	0,45mA
Inrush current I _{max} [A]:	25A
Inrush current time [μs]:	200μs
Manufacture:	Tridonic
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female
Length:	157mm
Height:	30mm
Width:	43mm
Weight:	0,1kg