



PRODUCT SHEET

Driver DALI 900mA Panel max 45W 18i5 DALI/EPN0034

Art. no: 0300-25



Driver DALI 900mA Panel max 45W 18i5 DALI/EPN0034



SPECIFICATIONS

System Power [W]:	45W
Dimming:	DALI2
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
Flickerfree:	Yes
CC or CV:	CC
CC [mA]:	350 - 1000mA
CC (forward voltage driver) [V]:	25 - 70V
Max output voltage [V]:	80
Output Current Tolerance [%]:	5%
Current Ripple [%]:	40%
Expected Lifetime:	100000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	8
Max load pr circuit - B16:	14
Max load pr circuit - C10:	18
Max load pr circuit - C16:	29
Leakage current [mA]:	0,7mA
Inrush current Imax [A]:	20A
Inrush current time [µs]:	300µs
Manufacture:	AcTEC
Manufacture P/N:	IE45D - Driver 350/400/500/600/700/800/
Primary Connection:	18i5 DALI male



PRODUCT SHEET

Driver DALI 900mA Panel max 45W 18i5 DALI/EPN0034

Art. no: 0300-25



Secondary Connection:	EPN0034 female
Length:	140mm
Height:	27mm
Width:	70mm
Weight:	0,25kg