



## PRODUCT SHEET

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034

Art. no: 0300-26



# Driver Phasecut 900mA Panel max 45W 25-50V 18i3 M



### SPECIFICATIONS

System Power [W]:	45W
Dimming:	Phase-Cut
CC or CV:	CC
CC [mA]:	900 - mA
CC (forward voltage driver) [V]:	25 - 50V
Max output voltage [V]:	60
Current setting:	None
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Inrush current I <sub>max</sub> [A]:	5A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Manufacture P/N:	D90045NT - Driver 900mA cc 45W Phasecut
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female
Color:	White
Length:	166mm
Height:	24mm
Width:	52mm
Weight:	0,2kg



## PRODUCT SHEET

Driver Phasecut 900mA Panel max 45W 25-50V 18i3 Male/EPN0034

Art. no: 0300-26



Operating Temperature [°C]:

-20 - 50