



PRODUCT SHEET

Driver Phasecut 500mA max 25W 25-50V 18i3&EPN0034

Art. no: 0300-28



Driver Phasecut 500mA max 25W 25-50V 18i3&EPN003



SPECIFICATIONS

System Power [W]:	25W
Dimming:	Phase-Cut
CC [mA]:	500 - mA
CC (forward voltage driver) [V]:	25 - 50V
Max output voltage [V]:	50
Output Current Tolerance [%]:	5%
Current Ripple [%]:	50%
Expected Lifetime:	30000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	5mA
Inrush current I _{max} [A]:	5A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Manufacture P/N:	D50025NT - Driver 500mA 25W (25-50) Phas
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female
Length:	120mm
Height:	28mm
Width:	45mm
Weight:	0,15kg



PRODUCT SHEET

Driver Phasecut 500mA max 25W 25-50V 18i3&EPN0034

Art. no: 0300-28



Operating Temperature [°C]:

-20 - 50