



PRODUCT SHEET

Driver DALI 500mA max 25W 20-50V 18i5 DALI/EPN0034

Art. no: 0300-31



Driver DALI 500mA max 25W 20-50V 18i5 DALI/EPN003



SPECIFICATIONS

System Power [W]:	25W
Dimming:	DALI
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC or CV:	CC
CC [mA]:	260 - 700mA
CC (forward voltage driver) [V]:	20 - 36V
Max output voltage [V]:	75
Output Current Tolerance [%]:	5%
Current Ripple [%]:	40%
Expected Lifetime:	50000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	11
Max load pr circuit - B16:	18
Max load pr circuit - C10:	24
Max load pr circuit - C16:	39
Leakage current [mA]:	0,7mA
Inrush current I _{max} [A]:	15A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Manufacture P/N:	IE25D - Driver 260/350/400/450/500/550/
Primary Connection:	18i5 DALI male
Secondary Connection:	EPN0034 female
Operating Temperature [°C]:	-20 - 50