



PRODUCT SHEET

Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0034

Art. no: 0300-48



Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0



SPECIFICATIONS

System Power [W]:	30W
Dimming:	Phase-Cut
Standby power P _{sb} (W) <:	0,5
Flicker metric (P _{st} LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC or CV:	CC
CV (driver) [V]:	33V
CC [mA]:	660 - 730mA
CC (forward voltage driver) [V]:	30 - 40V
Max output voltage [V]:	40
Output Current Tolerance [%]:	5%
Current Ripple [%]:	5%
Expected Lifetime:	50000h
System Voltage [V]:	230V 50HzV
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	33
Max load pr circuit - B16:	53
Max load pr circuit - C10:	33
Max load pr circuit - C16:	53
Leakage current [mA]:	0,5mA
Inrush current I _{max} [A]:	3,06A
Inrush current time [μs]:	224μs
Manufacture:	Up-Shine
Primary Connection:	18i3 male



PRODUCT SHEET

Driver Phasecut 700mA 30W phasecut 18i3 male/EPN0034

Art. no: 0300-48



Secondary Connection:

EPN0034 female