



FDV SPEC SHEET

Panel Circle 6050lm 840 Opal 39W WH 1m cable w/18i3

Art. no: 0794-01-3



Panel Circle 6050lm 840 Opal 39W WH 1m cable w/18i



Art. no: 0794-01-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4770
Lumen LED (tc=25):	6050
Beam Angle:	106x106°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
Lens (Diffuser):	Opal

MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Mounting:	Recessed, Ceiling

PRODUCT

Ingress Protection:	IP40
Impact Protection:	IK05
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	595
Height [mm]:	70
Width [mm]:	595
Weight [kg]:	3

ELECTRICAL DATA

Dimming:	None
System Power [W]:	39
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	31
Max load pr circuit - B16:	50
Max load pr circuit - C10:	46
Max load pr circuit - C16:	73
Inrush current I _{max} [A]:	5
Inrush current time [μs]:	50
Current Output [mA]:	950