



FDV SPEC SHEET
Circular Pendant
Art. no: 101305-120-2-ddd



Circular Pendant



Art. no: 101305-120-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen LED (tc=25): | 2200 |
| Beam Angle: | 120° |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 5 |
| Lens (Diffuser): | Opal |
| UGR (<=): | 22 |

MOUNTING / CONNECTION

| | |
|-------------|------------------|
| Connection: | Cable 2m |
| Mounting: | Pendant, Ceiling |

ELECTRICAL DATA

| | |
|---------------------|-----------|
| Dimming: | DALI2 |
| System Power [W]: | 20 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |



FDV SPEC SHEET

Sircular Pendant
Art. no: 101305-120-2-ddd



| PRODUCT | |
|-----------------------------|----------------|
| Ingress Protection: | IP20 |
| Impact Protection: | IK09 |
| Operating Temperature [°C]: | -30 - 55 |
| Lifetime [h]: | L80B20: 50 000 |
| Color: | Black |
| Length [mm]: | 60 |
| Height [mm]: | 60 |
| Diameter [mm]: | 450 |
| Weight [kg]: | 3,2 |
| Housing Material : | Aluminium |
| Diffuser Material: | Polycarbonate |