




FDV SPEC SHEET

Leila C Maxi Surface

Art. no: 101375-70-3



Leila C Maxi Surface



Art. no: 101375-70-3

LIGHT TECHNICAL

Lumen Output:	5731
Lumen LED (tc=25):	7200
Beam Angle:	70°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Ceiling, Surface

ELECTRICAL DATA

Dimming:	None
System Power [W]:	48
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	35
Max load pr circuit - B16:	65
Max load pr circuit - C10:	35
Max load pr circuit - C16:	65
Inrush current I _{max} [A]:	10
Inrush current time [μs]:	100
Socket / Cap-Base:	N/A
Current Output [mA]:	1200
Voltage Forward Min [V]:	30,6
Voltage Forward Max [V]:	39,3



FDV SPEC SHEET

Leila C Maxi Surface

Art. no: 101375-70-3



PRODUCT

To be recessed in insulation:	No
Ingress Protection:	IP20
Impact Protection:	IK00
Operating Temperature [°C]:	-25 - 50
Lifetime [h]:	L80B10: 60 000
Color:	White
Height [mm]:	150
Width [mm]:	230
Weight [kg]:	2,6