




FDV SPEC SHEET

Lorenzo II 930 20° 2W 2A-USB + USB-C BK 3m cable

Art. no: 101641-01-20-2



Lorenzo II 930 20° 2W 2A-USB + USB-C BK 3m cable



Art. no: 101641-01-20-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	130
Lumen LED (tc=25):	150
Beam Angle:	20°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Wall

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
System Power [W]:	2
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	40
Max load pr circuit - B16:	70
Max load pr circuit - C10:	72
Max load pr circuit - C16:	119
Inrush current I _{max} [A]:	15
Inrush current time [μs]:	50
Current Output [mA]:	300



FDV SPEC SHEET

Lorenzo II 930 20° 2W 2A-USB + USB-C BK 3m cable

Art. no: 101641-01-20-2



PRODUCT	
Ingress Protection:	IP20
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9016
Length [mm]:	70
Height [mm]:	210
Width [mm]:	68
Weight [kg]:	0,71
Housing Material :	Aluminium