



## FDV SPEC SHEET

Joule  
Art. no: 102018-03-2-ddd



## Joule



Art. no: 102018-03-2-ddd

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	7000
Beam Angle:	P3 Assymetric
CCT (Color Temperature):	4000
CRI / Ra:	90
Color Code:	940
MacAdam (SDCM):	5

### MOUNTING / CONNECTION

Connection:	Cable 5m
Mounting:	Mast, Wall

### ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	50
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	31
Max load pr circuit - B16:	50
Max load pr circuit - C10:	31
Max load pr circuit - C16:	50



## FDV SPEC SHEET

Joule

Art. no: 102018-03-2-ddd



PRODUCT	
Ingress Protection:	IP66
Impact Protection:	IK09
Corrosion Class:	C4
Wind force (EPA) [m2] at 0°:	0,15
Surge Protection:	L-N = 5KV, L/N-PE = 10KV
Operating Temperature [°C]:	-30 - 50
Lifetime [h]:	L80B10: 100 000
Color:	Grey
RAL:	RAL7022
Length [mm]:	615
Height [mm]:	225
Width [mm]:	350
Housing Material :	Aluminium