





FDV SPEC SHEET

Cylinder 45
Art. no: 102191-D2W-36-2-p



Cylinder 45



Art. no: 102191-D2W-36-2-p

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	460
Lumen LED (tc=25):	570
Beam Angle:	36
CCT (Color Temperature):	1800-3000K TW
Preset CCT (Color Temperature):	1800-3000K TW
CRI / Ra:	95
Color Code:	930-918
MacAdam (SDCM):	3
Lens (Diffuser):	Clear
UGR (<=):	19

MOUNTING / CONNECTION

Connection:	Track 1-Circuit
Mounting:	Track



FDV SPEC SHEET

Cylinder 45

Art. no: 102191-D2W-36-2-p



PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP20	Dimming:	Phase-Cut
Impact Protection:	IK02	Flickerfree:	Yes
Operating Temperature [°C]:	-20 - 45	Standby power Psb (W) <:	0,5
Lifetime [h]:	L80: 100 000	Flicker metric (Pst LM) <:	1
Color:	Black	Stroboscopic effect metric (SVM) <	0,4
RAL:	RAL9005	System Power [W]:	8
Length [mm]:	110	System Voltage [V]:	230V 50Hz
Height [mm]:	110	Dimming Output Type:	Amplitude Modulation
Diameter [mm]:	45	Dimming Phasecut Type:	Leading / Trailing edge
Weight [kg]:	0,2611111111111111	Protection Class:	2
Housing Material :	Aluminium	Max load pr circuit - B10:	75
Diffuser Material:	Aluminium	Max load pr circuit - B16:	120
Material 2:	Polycarbonate	Max load pr circuit - C10:	120
		Max load pr circuit - C16:	192
		Leakage current [mA]:	0,25
		Inrush current Imax [A]:	5
		Inrush current time [µs]:	8
		Socket / Cap-Base:	N/A
		Current Output [mA]:	350
		Voltage Forward Min [V]:	15,5
		Voltage Forward Max [V]:	18,8
		Emergency light [h]:	No Emergency light