



FDV SPEC SHEET

Rod Midi C

Art. no: 102314-30-2



Rod Midi C



Art. no: 102314-30-2

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 2990 |
| Lumen LED (tc=25): | 3881 |
| Beam Angle: | 30 |
| CCT (Color Temperature): | 3200 |
| CRI / Ra: | 90 |
| Color Code: | 932 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |
| UGR (<=): | 19 |

MOUNTING / CONNECTION

| | |
|-------------|-----------------|
| Connection: | Track 3-Circuit |
| Mounting: | Track |



FDV SPEC SHEET

Rod Midi C

Art. no: 102314-30-2



| PRODUCT | |
|-----------------------------|---------------|
| Ingress Protection: | IP20 |
| Impact Protection: | IK02 |
| Operating Temperature [°C]: | -20 - 45 |
| Lifetime [h]: | L80: 100 000 |
| Color: | Black |
| RAL: | RAL9005 |
| Height [mm]: | 115 |
| Diameter [mm]: | 97 |
| Weight [kg]: | 0,66 |
| Housing Material : | Aluminium |
| Diffuser Material: | Aluminium |
| Material 2: | Polycarbonate |

| ELECTRICAL DATA | |
|------------------------------------|--------------------|
| Dimming: | None |
| Flickerfree: | Yes |
| Standby power Psb (W) <: | 0,5 |
| Flicker metric (Pst LM) <: | 0,037 |
| Stroboscopic effect metric (SVM) < | 0,009 |
| System Power [W]: | 23 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Max load pr circuit - B10: | 56 |
| Max load pr circuit - B16: | 89 |
| Max load pr circuit - C10: | 56 |
| Max load pr circuit - C16: | 89 |
| Leakage current [mA]: | 0,55 |
| Inrush current Imax [A]: | 2,025 |
| Inrush current time [µs]: | 70 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 600 |
| Voltage Forward Min [V]: | 33 |
| Voltage Forward Max [V]: | 38 |
| Emergency light [h]: | No Emergency light |