





C Line







Lightsource Type: System Power [W]: CCT (Color Temperature): CRI / Ra: Lumen Output: Lumen LED (tc=25): Beam Angle: Lens (Diffuser): Dimming: Flickerfree: System Voltage [V]: Connection: Mounting: Lightsource Type: LED (replaceable) 60/50/42/33W 4000K 80 Lens (Diffuser): 10793lm 12100lm 90° Clear Dimming: None Flickerfree: Yes System Voltage [V]: Connection: Quickconnectx2 Mounting: Lifetime [h]: L80: 100 000h
CCT (Color Temperature): 4000K CRI / Ra: 80 Lumen Output: 10793lm Lumen LED (tc=25): 12100lm Beam Angle: 90° Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
CRI / Ra: 80 Lumen Output: 10793lm Lumen LED (tc=25): 12100lm Beam Angle: 90° Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Lumen Output: 10793lm Lumen LED (tc=25): 12100lm Beam Angle: 90° Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Lumen LED (tc=25): 12100lm Beam Angle: 90° Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Beam Angle: 90° Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Lens (Diffuser): Dimming: None Flickerfree: Yes System Voltage [V]: Connection: Quickconnectx2 Mounting: Lifetime [h]: Clear Que Clear Clear Clear Lifetime (Diffuser): Que Lifetime (Diffuser): Lifetime
Dimming: Flickerfree: Yes System Voltage [V]: Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: None Yes Cannection: Quickconnectx2 Lifetime [h]:
Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
System Voltage [V]: 230V 50Hz Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Connection: Quickconnectx2 Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Mounting: Ceiling, Surface Lifetime [h]: L80: 100 000h
Lifetime [h]: L80: 100 000h
Lawrence DW
Lumen/W: 180lm/W
MacAdam (SDCM): 3
Color: Steel
Length [mm]: 1250mm
Height [mm]: 50mm
Width [mm]: 76mm
Weight [kg]: 2,04kg



C Line is an industrial lighting fixture designed for ceiling mounting. The fixture has many applications, such as in industrial and warehouse settings. It features through-wiring (5×2.5 mm²), ensuring efficient and tool-free installation.