




FDV SPEC SHEET

Base 6000lm 840 Opal 45W IP69K L=1480mm 3m cable PMMA

Art. no: 10254834



Base 6000lm 840 Opal 45W IP69K L=1480mm 3m cabl



Art. no: 10254834

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	6000
Beam Angle:	90°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	3
Lens (Diffuser):	Opal

ELECTRICAL DATA

Dimming:	None
System Power [W]:	44
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	15
Max load pr circuit - B16:	24
Max load pr circuit - C10:	25
Max load pr circuit - C16:	40

MOUNTING / CONNECTION

Connection:	Cable 3m
Mounting:	Suspended, Surface, Wall



FDV SPEC SHEET

Base 6000lm 840 Opal 45W IP69K L=1480mm 3m cable PMMA
Art. no: 10254834



PRODUCT	
Ingress Protection:	IP66-69K
Impact Protection:	IK03
Operating Temperature [°C]:	-25 - 35
Lifetime [h]:	L80B10: 100 000
Color:	Grey
RAL:	RAL7035
Length [mm]:	1480
Height [mm]:	67
Width [mm]:	76
Weight [kg]:	2,3