



FDV SPEC SHEET

Tania Slim Bed

Art. no: 102660-2-36-2



Tania Slim Bed



Art. no: 102660-2-36-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	450
Lumen LED (tc=25):	500
Beam Angle:	34
CCT (Color Temperature):	2700
CRI / Ra:	90
Color Code:	927
MacAdam (SDCM):	2
Lens (Diffuser):	Clear
UGR (<=):	15

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Surface, Wall

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	4,5
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	40
Max load pr circuit - B16:	64
Max load pr circuit - C10:	64
Max load pr circuit - C16:	102



FDV SPEC SHEET

Tania Slim Bed

Art. no: 102660-2-36-2



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK01
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9006
Length [mm]:	188
Height [mm]:	100
Width [mm]:	100
Diameter [mm]:	42
Weight [kg]:	0,48