



PRODUCT SHEET


Cilla Midi

Art. no: 102730-30-2

NORLUX®

Lighting Solutions

Cilla Midi



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	13W
CCT (Color Temperature):	2700K
CRI / Ra:	90
Lumen Output:	1428lm
Lumen LED (tc=25):	2197lm
Beam Angle:	30
Lens (Diffuser):	Lens
Dimming:	Depending on Driver
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	18i3 Quick connection
Mounting:	Recessed
Cut-out [mm]:	75-80mmmm
Lifetime [h]:	L80: 100 000h
Lumen/W:	115lm/W
UGR (<=):	19
MacAdam (SDCM):	3
Color:	Black
Length [mm]:	90mm
Height [mm]:	91mm
Width [mm]:	90mm
Diameter [mm]:	90mm
Weight [kg]:	0,2944444444444444kg
Emergency light [h]:	No Emergency light
To be recessed in insulation:	Yes, recessed in insulation

Cilla Midi is an elegant and functional downlight, perfect for hotels or restaurants. It provides comfortable and atmospheric lighting with low glare, thanks to its high color rendering index of CRI 95 and a warm color temperature of 2700K or 3000K. With a recessed light source, it creates an inviting ambiance that highlights details. With a compact design measuring 90mm in diameter and 91mm in height, Cilla Midi integrates seamlessly into any room. Its IP44 rating ensures that the lamp is both dust and splash-resistant, making it ideal for various applications. Designed for recessed installation, it is supplied without a driver, which must be purchased separately. For added flexibility, you can choose between front rings in three different colors to match your interior style.

Cilla Midi the perfect combination of design, functionality, and quality.